




DIAPHRAGM Pumps

S. 340-AB

in aluminium

3/4" Ratio 1:1 Flow rate 70 l/min



The transfer diaphragm pumps, specific for oil and similar products in die-cast aluminium, with high-quality components, ensure lasting and reliable operation even in extreme conditions. Ideal for transferring fluids even in the presence of suspended solids.



series **340-AB**

Article with membrane in **NBR High Nitrile**



Compatible fluids		Water, mineral-vegetable oils, diesel oil		
Pump material		Aluminium		
Ball valve material		Hytrel		
Air inlet connection	bsp	F 3/8" G	F 3/8" G	F 3/8" G
Fluid inlet-outlet connection	bsp	F 3/4" x F 3/4" G	suction tube ø 34 mm - F 3/4" G	suction tube ø 34 mm - F 3/4" G
Air working pressure	bar	2 - 6	2 - 6	2 - 6
Air max pressure	bar	8	8	8
Average air consumption	l/min	500	500	500
Noise level	dB	75	75	75
Fluid temperature	°C	-10 +90	-10 +90	-10 +90
Max solids diameter	mm	ø 1,5	ø 1,5	ø 1,5

33/2011NHHV2

33500

33505

Suitable for drums or tanks



Suction-delivery ball valve with spring

Packing		N° - m ³	1 - 0,015	2 - 0,040	2 - 0,040
Weight		Kg	8	10	11
Dimensions (A - B - C)		cm	16 - 20 - 25,6	16 - 20 - 25,6	16 - 20 - 25,6
Suction tube length and ø		cm	-	94x3,4	124x3,4

